

FEATURES:

- Input: AC 100-240V~ 50/60Hz
- Available plug: C8 inlet
- Port: 4xTYPE C port
- Ovp, Ocp, Scp and Over load protection
- GAN TECH, 200W PD Charger, smart
- Efficiency level: VI
- Dimension: 88.0*107.5*35.0mm(exclude plug)
- Protocol: TypeC PD2.0/PD3.0/PD3.1/PPS, QC4/QC4+/QC3.0/QC2.0 , FCP, SCP, AFC, Apple2.4 , BC1.2, MTK



SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335, IEC60065
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55032 class B (CISPR32), EN61000-3-2,-3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2,3,4,5,6,8,11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

MODEL LIST:

MODEL	USB PORT	OUTPUT	Single Port POWER	TOTAL POWER
5U09T-GaN	USB C PORT 1	PD: 5V3A,9V3A,12V3A, 15V3A, 20V5A, 28V5A	140W	PD1+PD2/PD3 :140W+100W (240W Max)
	USB C PORT 2	PD: 5V3A,9V3A,12V3A, 15V3A, 20V5A(PPS:3.3-21V 5A)	100W	PD1+PD4/USBA:140W+30W (170W Max)
	USB C PORT 3	PD: 5V3A,9V3A,12V3A, 15V3A, 20V5A(PPS:3.3-21V 5A)	100W	PD2+PD3: 65W+30W (95W Max)
	USB C PORT 4	PD: 5V3A,9V3A,12V2.5A, 15V2A, 20V5A(PPS:3.3-11V3.0A)	30W	PD2/PD3+PD4/USBA:65W+30W(95W Max)
	USB A PORT 5	5V3A,5V4.5A,4.5V5A,9V3A,12V2.5A,15V2A,20V1.5A	30W	PD1+PD2+PD3+(PD4+USBA): 140W+45W+30W+15W(230W Max)

Mechanical Diagram:

