

FEATURES:

- Input: AC 100-240V~ 50/60Hz
- Available plug: US, EU, US foldable plug
- Power: 45W PD Charger
- Ovp, Ocp, Scp and Over load protection
- GAN TECH, PD Charger, smart
- Efficiency level: VI
- Dimension: 73.4*45.3*31mm
- Application: Tablet, Mobile phone, etc...



SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335, IEC60065
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55032 class B (CISPR32), EN61000-3-2, -3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

MODEL LIST:

MODEL	USB PORT	OUTPUT	Single Port POWER	TOTAL POWER
Pd0651	USB C PORT 1	PD: 5V3, 9V3A, 12V3A, 15V3A, 20V3.25A PPS: 5-21V 3A	65W	45W
	USB C PORT 1	PD: 5V3, 9V3A, 12V3A, 15V3A, 20V3.25A PPS: 5-21V 3A	65W	
	USB A PORT 3	5V3.0A.9V2.0A.12V1.5A	18W	
MODEL	USB PORT	OUTPUT	Single Port POWER	TOTAL POWER
Pd0650	USB C PORT 1	PD: 5V3, 9V3A, 12V3A, 15V3A, 20V3.25A PPS: 5-11V 4.05A	65W	65W
	USB A PORT 1	5V3.0A.9V2.0A.12V1.5A	18W	
MODEL	USB PORT	OUTPUT	Single Port POWER	TOTAL POWER
Pd0652	USB C PORT 1	PD: 5V3, 9V3A, 12V3A, 15V3A, 20V3.25A PPS: 5-11V 4.05A	65W	65W
	USB C PORT 1	PD: 5V3, 9V3A, 12V3A, 15V3A, 20V3.25A PPS: 5-11V 4.05A	65W	

Mechanical Diagram:

